Certificate of Compliance

Certificate Number:
UL-US-L511681-11-90600202-4

Report Reference:
E511681-20200609

Issue Date:
2024-04-19

Issued to:

PHOENIX CONTACT ASIA-PACIFIC (NANJING) CO LTD
JIANGNING DEVELOPMENT ZONE
36 PHOENIX RD
PO BOX 236 JIANGNING NANJING NANJING, Jiangsu Sheng 211100
China

This certificate confirms that representative samples of:

BBTH2 - Intercell and Intertier Connectors for Use in Electrochemical Battery System Applications - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 4128, 5th Ed., Issue Date: 2020-05-13

Additional Information:
See UL Product iQ® at https://iq.ulprospector.com for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.

David Piecuch
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at https://www.ul.com/contact-us.

© 2024 UL LLC. All rights reserved.

CERTIFICATE OF COMPLIANCE

Certificate number	UL-US-L511681-11-90600202-4
Report reference	E511681-20200609
Date	2024-04-19



David Piecuch
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at https://www.ul.com/contact-us.

© 2024 UL LLC. All rights reserved.
Form-ULID-013925-CoCa – ver 1.0

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L511681-11-90600202-4
Report reference E511681-20200609
Date 2024-04-19

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
ES-BPC-C 16-25 BK, may be followed by suffix, which represents the client code.	Cable Connector
ES-BPC-C 16-25 OG, may be followed by suffix, which represents the client code.	Cable Connector
ES-BPC-C 35 BK, may be followed by suffix, which represents the client code.	Cable Connector
ES-BPC-C 35 OG, may be followed by suffix, which represents the client code.	Cable Connector
ES-BPC-C 35 RD, may be followed by suffix, which represents the client code.	Cable Connector
ES-BPC-C 50-70 BK, may be followed by suffix, which represents the client code.	Cable Connector
ES-BPC-C 50-70 OG, may be followed by suffix, which represents the client code.	Cable Connector
ES-BPC-C 50-70 RD, may be followed by suffix, which represents the client code.	Cable Connector
ES-BPC-C 95-120 BK, may be followed by suffix, which represents the client code.	Cable Connector
ES-BPC-C 95-120 OG, may be followed by suffix, which represents the client code.	Cable Connector
ES-BPC-C 95-120 RD, may be followed by suffix, which represents the client code.	Cable Connector
ES-BPC-NC 50 BK, may be followed by suffix, which represents the client code.	Cable Connector
ES-BPC-NC 50 OG, may be followed by suffix, which represents the client code.	Cable Connector
ES-FT-BPC-B 16-25 BK, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-B 16-25 OG, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-B 35-70 BK, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-B 35-70 OG, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-B 35-70 RD, may be followed by suffix, which represents the client code.	Panel Mounted Inlet

David Piecuch
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at https://www.ul.com/contact-us.

© 2024 UL LLC. All rights reserved.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L511681-11-90600202-4
Report reference E511681-20200609
Date 2024-04-19

ES-FT-BPC-B 95-120 BK, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-B 95-120 OG, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-B 95-120 RD, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-B/S 16-25 BK, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-B/S 16-25 OG, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-B/S 35-70 BK, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-B/S 35-70 BK GX, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-B/S 35-70 OG, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-B/S 35-70 OG GX, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-B/S 35-70 RD, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-B/S 95-120 BK, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-B/S 95-120 BK SG, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-B/S 95-120 OG, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-B/S 95-120 OG SG, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-B/S 95-120 RD, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-C 16-25 BK, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-C 16-25 OG, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-C 35 BK, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-C 35 BK SG, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-C 35 OG, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-C 35 OG SG, may be followed by suffix, which represents the client code.	Panel Mounted Inlet

David Piecuch
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at https://www.ul.com/contact-us.

© 2024 UL LLC. All rights reserved.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L511681-11-90600202-4
Report reference E511681-20200609
Date 2024-04-19

ES-FT-BPC-C 35 RD, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-C 50-70 BK, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-C 50-70 OG, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-C 50-70 RD, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-C 95-120 BK, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-C 95-120 OG, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-C 95-120 RD, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-S 16-25 BK, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-S 16-25 OG, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-S 35-70 BK, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-S 35-70 OG, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-S 35-70 RD, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-S 95-120 BK, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-S 95-120 OG, may be followed by suffix, which represents the client code.	Panel Mounted Inlet
ES-FT-BPC-S 95-120 RD, may be followed by suffix, which represents the client code.	Panel Mounted Inlet

David Piecuch
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at https://www.ul.com/contact-us.

© 2024 UL LLC. All rights reserved.